

# Lumens®

Your Success, Our Passion!



The Lumens<sup>®</sup> VC-B11U delivers brilliantly sharp and exceptional video with 4K Ultra HD image quality. The VC-B11U's genius auto framing function can automatically frame all participants in a perfect view. It features 120° field-of-view wide-angle providing an excellent visual collaboration experience. Thanks to its built-in two Omni-directional microphones, it can capture crystal-clear voice. It's applicable for video conference with 3-10 participants in the small-to-medium size room.

### **Key Features**

- Clear images with 4K sensor, fixed-lens, and WDR
- Effectively capture human voice up to 5 meters
- · Hands-free auto framing to include all participants in a perfect view
- Easily control the camera by a mini remote controller or software

### **Key Feature Details**



#### 🔋 Crystal-clear Video

The VC-B11U provides crystal-clear video with professional 4K sensor and the advanced WDR technology. It ensures everyone to be seen clearly and perfectly.



### **Genius Auto Framing**

Genius and accurate auto framing can detect everyone in wide angle. Ensure all participants are framing perfectly on a screen.



#### **Built-in Microphones**

The VC-B11U with high sensitive dual-microphone can effectively captures human voice up to 5 meters, allowing everyone to be heard clearly.



### Easy Camera Control

Easy control like auto framing, preset and ePTZ function by the compact remote controller. Customize the image quality with Lumens exclusive software.

# **Applications**



**Distance Learning** 





Video Conference

### **Product Specifications**

Sensor 1/2.8" 8.57MP CMOS   Video Format 3840x2160 30/25 fps 1920x1080 30/25 fps 1280x720 30/25 fps 640x360 30/25 fps   Video Octoor Instant USB 3.0 Type C	
Video Format 1920x1080 30/25 fps 1280x720 30/25 fps 640x360 30/25 fps	
LISB 3.0 Type C	
Video Output Interface (USB 2.0 Compatible)	
Pixel Zoom 1080p: 2x / 720p: 3x	
Digital Zoom 16x	
Viewing Angle 120°	
PTZ ePTZ	
Auto Framing Yes (1080p and below)	
Auto Framing Maximum Distance 5 Meters	
Aperture F 2.2	
Focal Length f=2.1mm	
<b>Shutter Speed</b> 1/30 ~ 1/10000	
Minimum Object Distance 500 mm	
Video S/N Ratio > 50dB	
Minimum Illumination 10 lux	
Gain Control Auto / Manual	
White Balance Auto / Manual / One push	

Brightness Control	Yes
Exposure Control	Auto / Manual / Shutter Pri
WDR	Yes
2D NR	Yes
3D NR	Yes
Image Flip	Mirror / Flip
Preset Positions	64
Control Interface	USB
Control Protocol	UVC / UAC
Video Compression	YUY2 / MJPEG / H.264 / NV12
Built-in Mic	2 Omni-directional Mics
Mic Effective Distance	5 Meters
IR Receiver	Yes
IR Remote Control	Yes
Power Consumption	< 4.5W (5V @0.9A)
Mounting	Tripod-Ready Universal Clip
Weight	1.1 lbs (0.5kg)
Dimensions	Without Clip: 1.2" x 8.3" x 1.4" (30 x 210 x 35 mm) With Clip: 1.9" x 8.3" x 2.9" (47.4 x 210 x 73.6 mm )

## **Compatible Software**









Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone : +1-888-542-3235 Fax : +1-510-252-1389 Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone : +32-473-58-38-95 Fax : +32-2-452-76-00



www.MyLumens.com