



| TR-004 | |
|--|---|
| CPU | Micro processor with hardware RAID |
| Drive Bay | 4 x 3.5-inch SATA 3Gb/s |
| Drive Compatibility | 3.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s solid state drives |
| Hot-swappable | Yes |
| USB 3.2 Gen 1 port | 1 x Type-C USB 3.2 Gen 1 (USB 3.2 Gen 1) |
| Form Factor | Tower |
| Dimensions (HxWxD) | 168.5 × 160.2 × 219 mm |
| Weight (Net) | 1.85 kg |
| Max. number of HDDs/SSDs supported | 4 |
| Hard Drive Type | 4 x 2.5-inch or 3.5-inch SATA 3Gb/s |
| Operating temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | External Power Adapter, 65W, 100-240V |
| Power Consumption: HDD Sleep Mode | 4.17 W |
| Power Consumption: Operating Mode, Typical | 18.21 W |
| Fan | 1 x 120mm, 12VDC |
| Sound Level | 18.1 db(A) |
| System Warning | Buzzer |
| Kensington Security Slot | Yes |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory

slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.