ClickShare Bar Core

Premium video bar for engaging, effortless wireless conferencing



- Crystal-clear, highquality stereo audio
- Advanced AI-powered 4K camera
- Simplified installation
- Sound investment: fewer interventions, minimized downtime, future-proof platform
- Carbon-neutral product

ClickShare Bar Core is a carbon-neutral, all-in-one video bar that enables engaging, effortless wireless conferencing in small and medium-sized meeting rooms with any videoconferencing platform. This solution ensures meeting participants feel heard and seen thanks to its high-quality AV capabilities while offering simplified installation and reduced Total Cost of Ownership.



Operating system Windows 10 and higher macOS 11 (Ventura) and higher Android VL3 and higher (ClickShare Appl IOS 16 and higher (ClickShare Appl IOS 16 and higher (ClickShare Appl IOS 16 and higher (ClickShare Appl IOS Ventura latest build commended. Intel 15 dual-core processor / 8GR RNM / OS Windows 10 latest build or Mac OS tentura latest build and Mac OS tentura latest build for Mac OS tentura latest	Product specifications	CLICKSHARE BAR CORE
System requirements 16 and higher (CilciGhare App) System requirements For a smooth experience with Microsoft Teams or Zoom Minimum. Intel 13 dual-core processor / 8GB RM/ / OS. Windows 10 latest build or Mac OS latest build Video outputs 4K UHD (S840*2160) (a 30Hz HDMI 14b or US8-C DP ALT mode (DisplayPort 1.2) Video inputs	General specifications	
RAM / OS: Windows 10 latest build or Mac OS Ventura latest build Recommended Intel 15 4-core processor / 8GB RAM / OS Windows 11 latest build or Mac OS latest build Video outputs 4k UHD (3840*2160) @ 30Hz. HDMI 14b or USB-C DP ALT mode (DisplayPort 12) Video inputs - Camera 4k camera, 3x zoom/ePTZ, 120lFOV Camera AI Group framing and composition mode with up to 4 people Audio output 2x 10W full duplex and stereo speakers, 8 Ohms impedance Audio pickup 6 beamforming MEMS microphones with echo and background noise cancellation. Pickup range up to 15 feet / 4.5 meters ClickShare Buttons 1 ClickShare Buttons 1 ClickShare Buttons 1 ClickShare App Desktop & Mobile Native protocols Airplay, Geogle Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode	Operating system	
Video inputs - Camera 4K camera, 3x zoom/ePTZ, 1200FOV Camera Al Group framing and composition mode with up to 4 people Audio output 2x 10W full duplex and stereo speakers, 8 Ohms impedance Audio pickup 6 beamforming MEMS microphones with echo and background noise cancellation. Pickup range up to 15 feet / 4.5 meters ClickShare Buttons 1 ClickShare App Desktop & Mobile Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Farless Wireless transmission protocol IEEE 802.11 al/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare But Wireless transmission protocol IEEE 802.11 al/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare But Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN IGbit, 1x USB-C 2.0 (side) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN IGbit, 1x USB-C 2.0 (side) Temperature range Operating, 0°C to +40°C (+32°F to +104°F) Max. 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Max. 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Max. 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Max. 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Max. 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Max. 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Max. 35°C (95°F) at 3000m Storage: -20°C to +6	System requirements	RAM / OS: Windows 10 latest build or Mac OS Ventura latest build Recommended: Intel i5 4-core
Camera 4K camera, 3x zoom/ePTZ.1200FOV Camera Al Group framing and composition mode with up to 4 people Audio output 2x 10W full duplex and stereo speakers. 8 Ohms impedance Audio pickup 6 beamforming MEMS microphones with echo and background noise cancellation. Pickup range up to 15 feet / 4.5 meters ClickShare Buttons 1 ClickShare App Desktop & Mobile Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WEP2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max: 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 CHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN IGbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Autioity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Contextions FCC/CE Fouch screen support 6 Interactivity <td>Video outputs</td> <td>4K UHD (3840*2160) @ 30Hz. HDMI 1.4b or USB-C DP ALT mode (DisplayPort 1.2)</td>	Video outputs	4K UHD (3840*2160) @ 30Hz. HDMI 1.4b or USB-C DP ALT mode (DisplayPort 1.2)
Camera Al Group framing and composition mode with up to 4 people Audio output 2x 10W full duplex and stereo speakers, 8 Ohms Impedance Audio pickup 6 beamforming MEMS microphones with echo and background noise cancellation. Pickup range up to 15 feet / 4.5 meters ClickShare Buttons 1 ClickShare App Desktop & Mobile Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHZ (DFS channels supported in select number of countries in network Integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Operating: Or to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage20°C to +60°C (-4°F) Humidity Storage. 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Cartifications FCC/CE Touch screen support 6 Interactivity No Wireless conferencing via App or Button	Video inputs	-
Audio output 2x 10W full duplex and stereo speakers, 8 Ohms impedance Audio pickup 6 beamforming MEMS microphones with echo and background noise cancellation. Pickup range up to 15 feet / 4.5 meters ClickShare Buttons 1 ClickShare App Desktop & Mobile Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Connections 1x USB-C 3.1 (DP) to screen. 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Operating. OP: C to +40°C (to +32°F to +104°F) Max: 35°C (95°F) at 3000m Storage20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Certifications FCC/CE Touch screen support 6 Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Camera	4K camera, 3x zoom/ePTZ, 1201FOV
Audio pickup 6 beamforming MEMS microphones with echo and background noise cancellation. Pickup range up to 15 feet / 4.5 meters ClickShare Buttons 1 ClickShare App Desktop & Mobile Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 // ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHZ (DPS channels supported in select number of countries in network integration mode) Connections Ix USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Mati-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support 6 Interactivity No Wireless conferencing Via App or Button Local view Yes Network connection LAN 6 WiFi	Camera Al	Group framing and composition mode with up to 4 people
to 15 feet / 4.5 meters ClickShare Buttons 1 ClickShare App Desktop & Mobile Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 31 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN IGbit, 1x USB-C 2.0 (side) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-thef system Kensington lock (back and bottom) Certifications FC/CE Touch screen support Ø Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN Ø WiFi	Audio output	2x 10W full duplex and stereo speakers, 8 Ohms impedance
ClickShare App Desktop & Mobile Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0*C to +40*C (+32*F to +104*F) Max: 35*C (95*F) at 3000m Storage: -20*C to +60*C (-4*F to +140*F) Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Audio pickup	
Native protocols Airplay, Google Cast, Miracast (available mid 2024) Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHz (DPS channels supported in select number of countries in network integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F) to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	ClickShare Buttons	1
Noise Level Fanless Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHZ (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 31 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	ClickShare App	Desktop & Mobile
Authentication protocol WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Anti-thef system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support 6 Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Native protocols	Airplay, Google Cast, Miracast (available mid 2024)
integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes	Noise Level	Fanless
Reach Max. 30m (100 ft) between ClickShare Button and ClickShare Bar Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Authentication protocol	
Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries in network integration mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Wireless transmission protocol	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
mode) Connections 1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Reach	Max. 30m (100 ft) between ClickShare Button and ClickShare Bar
Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Frequency band	
to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Connections	1x USB-C 3.1 (DP) to screen, 1x USB-A 2.0, 1x Ethernet LAN 1Gbit, 1x USB-C 2.0 (side)
condensing Anti-theft system Kensington lock (back and bottom) Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Temperature range	
Certifications FCC/CE Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Humidity	
Touch screen support & Interactivity No Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Anti-theft system	Kensington lock (back and bottom)
Wireless conferencing via App or Button Local view Yes Network connection LAN & WiFi	Certifications	FCC/CE
Local view Yes Network connection LAN & WiFi	Touch screen support & Interactivity	No
Network connection LAN & WiFi	Wireless conferencing	via App or Button
	Local view	Yes
Management and reporting Ves	Network connection	LAN & WiFi
	Management and reporting	Yes
Warranty 1 year standard. 5 years coverage via SmartCare	Warranty	1 year standard. 5 years coverage via SmartCare

Last updated: 13 Dec 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

BARCO