

Delock 3.5" USB 3.2 Gen 2 Front Panel 2 x USB Type-C™ + 2 x USB Type-A

Description

This front panel by Delock can be installed into a free 3.5" bay of a computer. It has two USB Type-A and two USB Type-C™ ports. It will be connected to the motherboard internally via a USB Type-E Key A male port.



Item no. 64057

EAN: 4043619640577

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - external:
 - 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
 - 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female
 - internal:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) key A male
 - 1 x SATA 15 pin plug (power supply)
- Data transfer rate up to:
 - SuperSpeed USB 10 Gbps,
 - SuperSpeed 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- Cable data:
 - 1 x USB 3.2 key A male, length ca. 38 cm (without connector)
 - 1 x power cable SATA 15 pin plug, length ca. 8 cm (without connector)
- Housing material: plastic
- Colour: black
- Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC with one free 3.5" bay
- Motherboard with a free USB key A female port
- Power supply with SATA 15 pin receptacle

Package content

- 3.5" front panel
- Screws
- User manual

Images



General

Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.3 or above Windows 10 64-Bit Windows 8.1 64-Bit Windows 11

Interface

External:	2 x USB 10 Gbps USB Type-C™ female 2 x USB 10 Gbps Type-A female
Internal:	1 x SATA 15 pin power connector 1 x USB 10 Gbps Key A Stecker

Technical characteristics

Data transfer rate:	up to 10 Gbps
---------------------	---------------

Physical characteristics

Housing material:	Plastic
Colour:	black

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de