



Galil 4-CO

4-Inch, 2-Way Open-Back Ceiling Speakers

| Speakers



The Galil 4-CO is a pair of two-way, open-back, 8 Ω speakers designed for mounting in the ceiling. The speakers feature a multi-tap power transformer for selecting 8 Ω or 70V/100V power settings suitable for array installation

FEATURES

Type - 2-way coaxial speaker

Woofers - 4" polypropylene cone

Tweeter - 0.5" Mylar dome

Frequency Response - 80Hz to 20kHz@ ± 3 dB

Impedance - 8 Ω

Power Handling - 15W RMS, 40W continuous program

Transformer Taps - 70V: 15W/7.5W/3.7W/Off (Lo-Z); 100V: 15W/7.5W/Off (Lo-Z)

Package Includes - 2 speakers (1 pair), cutout template and user manual

Mounting Bracket (Optional) - SKIC-4



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|--|
| DESCRIPTION: | 2-way open-back ceiling speakers |
| FREQUENCY RESPONSE: | 60Hz to 20kHz @-10dB, 80Hz to 20kHz @±3dB |
| WOOFER: | 4" (103mm) polypropylene with rubber surround |
| TWEETER: | 0.5" (13mm) Mylar |
| IMPEDANCE: | 8Ω (transformer tap in off position) |
| TRANSFORMER TAPS: | 70V-15W/7.5W/3.7W/Off (Lo-Z), 100V-15W/7.5W/Off (Lo-Z) |
| SENSITIVITY: | 83dB SPL, 1W@1m |
| MAX SPL: | Continuous: 95dB; peak: 98dB |
| POWER HANDLING: | 15W RMS, 40W continuous program |
| CROSSOVER FREQUENCY: | 13kHz |
| COVERAGE ANGLE: | 104° |
| DIRECTIVITY FACTOR (Q): | 8 averaged 1kHz to 10kHz |
| DIRECTIVITY INDEX (DI): | 9dB averaged 1kHz to 10kHz |
| INPUT CONNECTOR: | Terminal block |
| MATERIALS: | Frame, aluminum grill, safety cord attached to grill |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| WEIGHT PER SINGLE SPEAKER: | 0.95kg (2.09lbs) approx |
| SHIPPING WEIGHT (FOR PAIR): | 2.6kg (5.73lbs) approx |
| INSTALLATION CLEARANCE: | Mounting depth: 6.82cm (2.7") |
| CUTOUT DIAMETER | 13.9cm (5.47") |
| OPTIONAL ACCESSORIES: | SKIC-4 installation bracket |
| COLORS: | Available in white |