



# kramer

## KAC-CAM-70

PTZ Camera

---



The KAC-CAM-70 is a Microsoft certified cutting-edge dual 4K lens PTZ video camera for medium to large meeting spaces.

Featuring a 12x optical zoom close-up lens, a second wide angle 119° DFOV panoramic lens, and an integrated microphone array for direction assistance, the KAC-CAM-70 ensures an exceptional video experience for all participants. Its advanced AI-driven features, including auto-framing, speaker tracking, and advanced smart gallery, ensure that remote participants can clearly see the full expressions of everyone in the conference room, even those seated at a distance.

What sets the KAC-CAM-70 apart is its superior wide-angle sensor, which, when paired with our KAC-CU-200 MTR system, it provides a complete room view alongside a focused PTZ stream. Both video feeds are efficiently managed by the KAC-CU-200, ensuring seamless coverage for an exceptional meeting experience.

Designed to complement Kramer's solution bundles for medium-large Microsoft Teams Rooms, the KAC-CAM-70 plays a pivotal role in creating a highly optimized environment for hybrid Teams meetings

## FEATURES

---

- Enhance your meetings with advanced AI-powered features for a dynamic and engaging experience
- Perfect for hybrid sessions, ensuring every participant is clearly seen and heard, no matter their location
- Integrates seamlessly with Kramer AudioCodes MTR systems for a smooth and efficient hybrid video conferencing experience
- Effortless installation and operation using the KAC-TCH-10 room controller



# kramer

## TECHNICAL SPECIFICATIONS

---

Camera	<p>Image Sensor 1/1.8", high quality 4K CMOS sensor</p> <p>Effective Pixels 8.42M</p> <p>Lens Zoom Optical 12x, Digital: 16x</p> <p>Focal Length f= 4.8mm ~ 57.8mm</p> <p>Aperture F1.8 ~ F3.6</p> <p>Minimum Illumination 0.5Lux @ (F1.8, AGC ON)</p> <p>Shutter 1/30s ~ 1/10000s</p> <p>White Balance Auto, indoor, outdoor, one-touch, manual, variable color temperature</p> <p>Backlight Compensation Support</p> <p>Digital Noise Reduction 2D &amp; 3D</p> <p>Signal-to-Noise Ratio <math>\geq 55</math>dB</p> <p>Angle of View HFOV: <math>80^\circ \sim 7.54^\circ</math>, VFOV: <math>49.2^\circ \sim 4.34^\circ</math></p> <p>Motorized Pan &amp; Tilt Pan <math>\pm 170^\circ</math>, Tilt: <math>\pm 90^\circ</math></p> <p>Image Sensor 1/2.8 inch, CMOS, Effective pixel: 8.46M</p> <p>Focal Length f=1.97mm</p> <p>Field of View HFOV: <math>107^\circ</math></p> <p>Minimum Illumination 0.5 Lux @ (F1.8, AGC ON)</p> <p>Shutter 1/30s ~ 1/10000s</p> <p>Digital Noise Reduction 2D &amp; 3D</p> <p>Privacy Shutter Electric</p>
USB	<p>Video Compression YUV / H.264 / MJPEG</p> <p>USB Protocol USB 3.0, USB UVC</p> <p>Video Format (USB 3.0) H.264 / MJPEG: 4KP30, 4KP25, 1080P30, 1080P25, 720p/30, 720p/25, 1024x576P30, 1024x576P25, 960x540P30, 960x540P25, 800x600P30, 800x600P25, 640x480P30, 640x480P25, 640x360P30m, 640x360P25, 480x270P30, 480x270P25, 352x288P30, 352x288P25, 320x240P30, 320x240P25 YUV: 1080P30, 1080P25, 720p30, 720p25, 360P30, 360P25</p>
Microphone	<p>Quantity 3</p> <p>Pickup angle <math>180^\circ</math></p>
Camera modes	<p>Presenter Tracking, Auto Framing, Smart Gallery, Speaker tracking, Multi Stream, Manual</p>
Algorithm support range	<p>1~8m</p>
Smart Gallery maximum number of feeds	<p>8</p>

I/O	LAN port ×1, RJ45, POE+
	USB port ×1, USB 3.0, Type-C
	Audio port (Future use) ×1, 3.5mm
	Power port ×1, DC-005/Φ2.0 type (DC IN 12V/2A)
General	Input voltage DC 12V/PoE+ (802.3at)
	Input current 2A
	Operating temperature -10°C ~ 40°C
	Stored temperature -40°C ~ 60°C
	Power consumption ~20W
	Dimension L×H×D 181×151.5×178.4mm
	Dimension (package) L×W×H 295×245×240mm
	Net Weight 2.3kg
	Security Kensington lock
	Accessories USB cable (A-C) 2m, wall mount bracket, power adaptor, remote control
Product Dimensions	46.00cm x 9.70cm x 7.30cm (18.11" x 3.82" x 2.87" ) W, D, H
Product Weight	1.1kg (2.3lbs) approx
Shipping Dimensions	53.00cm x 16.50cm x 15.70cm (20.87" x 6.50" x 6.18" ) W, D, H
Shipping Weight	2.4kg (5.2lbs) approx