

# NPD-6001C-E Midspan bt 60W IP67

## PoE Midspan



- ▶ Makes PoE cameras easy to install
- ▶ Plug-and-play installation
- ▶ For outdoor usage
- ▶ One part-number for worldwide use (AC connector)
- ▶ Includes integrated 6kV surge protection

The PoE Midspan for outdoor installations enables remote PoE power for various Bosch IP PTZ cameras. The PoE Midspan generates a maximum of 60 W and complies to the IEEE 802.3 af/at/bt standards. The PoE Midspan also offers surge protection for both the AC and the PoE ports to protect the indoor equipment from outdoor power surges.

### Regulatory information

Standard	Type
Regulatory compliance	IEEE 802.3bt type 3 RoHS compliant WEEE compliant CE
Electromagnetic emission & immunity	FCC Part 15, Class B EN 55032 Class B (emissions) EN 55024 EN61000-4-5: Class 5 (AC lines 6kV CM/DM) VCCI
Surge protection	Design to meet surge protection as specified in: GR-1089-CORE Issue 4 ITU-T K.21 enhanced surge level protection (6 kV on data and AC lines)
Safety	UL/IEC/EN 60950-1 (ed.2) UL 60950-22

Standard	Type
Other standards and approvals	Dust proof and water resistance: EN60529 Approvals level IP67 NEMA 250, Level 4X ASTM B-117 corrosion resistance

Region	Regulatory compliance/quality marks
Europe	CE

### Parts included

Quantity	Component
1	PoE Midspan
1	Waterproof gland
1	Quick installation guide

### Technical specifications

#### Electrical

PoE input	Supports IEEE 802.3bt type 3 standard PDs
PoE output pin assignment and polarity	4/5 (+), 7/8 (-), 1/2(-), 3/6(+)
PoE output power voltage (VDC)	54 VDC
PoE output user port power (W)	60 W (guaranteed)
Input voltage (VAC)	100 VAC – 240 VAC (± 10%)

Input current (A)	2 A at 100 - 240 VAC
AC frequency (Hz)	50 - 60 Hz
Maximum heat loss (BTU/h)	35 BTU/h

### Connectivity

Number of ports	1
Data rates (Mbps)	10/100/1000 Mbps
Connectors	Shielded RJ-45 (with gasket), AC connector
Reliability	MTBF: 200,000 h at 25 °C

### Mechanical

#### Environmental

Operating temperature (°C)	-40 °C – 65 °C
Operating temperature (°F)	-40 °F – 149 °F
Storage temperature (°C)	-40 °C – 85 °C
Storage temperature (°F)	-40 °F – 185 °F
Operating relative humidity, non-condensing (%)	95%
Storage relative humidity (%)	95%
Maximum operating altitude (m)	2000 m
Maximum operating altitude (ft)	6560 ft
Usage	Outdoor

### Construction

Dimensions (H x W x D) (mm)	60 mm x 140 mm x 170 mm
Dimensions (H x W x D) (in)	2.36 in x 5.51 in x 6.69 in
Weight (g)	1400 g
Weight (lb)	3.08 lb
Color	White

### Ordering information

#### NPD-6001C-E Midspan bt 60W IP67

Outdoor midspan with Power-over-Ethernet for use with PoE-enabled cameras; 60 W, single-port  
Order number **NPD-6001C-E | F.01U.398.267**

### Accessories

#### NDA-6090-PMA Pole mount for midspan bt outdoor

Pole mount for outdoor PoE midspans NPD-6001C-E / NPD-6001C-EBT and NPD-9001-E / NPD-9001-EBT  
Order number **NDA-6090-PMA | F.01U.402.626**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Tel.: +49 (0)89 6290 0  
Fax: +49 (0)89 6290 1020  
[de.securitysystems@bosch.com](mailto:de.securitysystems@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
[onlinehelp@us.bosch.com](mailto:onlinehelp@us.bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)