


NEC LED-E012i-217
Indoor LED 1.2 mm 217" UHD Bundle

Datasheet





Large Image Presentation, Small Budget Preservation

Bringing all the advantages of fine-pitch LED to more cost-conscious applications in corporate meeting rooms and digital signage, the E series lacks nothing in high impact content delivery. The pre-bundled solution includes everything you need to implement large surface visualisation without hindrance from bezels, with superb brightness and high contrast which gets noticed even in areas of high ambient light.

Designed for quick and easy set-up, the product is light weight and super slim for unobtrusive integration either free-standing or wall mounted. Front serviceable, all components are easily accessed for maintenance.

As you would expect from a quality manufacturer, there is no compromise to reliability, longevity and safety in offering this low-cost solution. Consistent with all LED products from Sharp/NEC, the chassis is of metal construction.

Benefits

Low-profile integration – the super slim and light weight modules align with perfection to create a large digital canvas which integrates unobtrusively into any environment.

Front serviceable modules - with front access to the LED modules, maintenance is easy.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with minimal gap necessary due to very low heat emission.

Care-free installation – with bundled solutions that deliver all you need to get your LED video wall up and running.

Product Information

Product Name	NEC LED-E012i-217
Product Group	Indoor LED 1.2 mm 217" UHD Bundle
Order Code	81000342

Display

Pixel Configuration	3-in-1 SMD (Black)
LED type	SMD (1010)
Screen Size [inch/cm]	217 / 551.18
Aspect Ratio	16:9
Pixel Pitch [mm]	1.2
Brightness (max.) [cd/ m²]	600
Lifetime	100000 hrs (50% brightness)
Contrast Ratio (typ.)	5000:1
Viewing Angle [°]	170 horizontal / 160 vertical
Dimming Capability	256 levels
Colour Processing	16 bit
Colours [Trill.]	281 trillion
LED Driving Method	1/45 dynamic scan
Frame Rate [Hz]	50/60
Refresh Rate [Hz]	≤ 3840
Colour Temperature [K]	3000 - 9500

Screen Resolution

Resolution	3840 x 2160
Resolution per m ²	640000
Number of Pixel per module [dot]	480 x 270
Number of Pixel per card [dot]	120 x 270

Connectivity

Input Video Digital	1 x 3G SDI; 1 x DVI-D; 1 x HDMI
Input Control	1 x GenLock; 1 x LAN

Electrical

Total Power	3776 typ. / 8000 max.	
Consumption [W]		

Power Consumption	291 per m² (normal use)		
typ. [W]			
Power Consumption max. [W]	617 per m²		
Power Consumption typ. [BTU]	991 per m² (normal use)		
Power Consumption max. [BTU]	2099 per m²		
Environmental Cond	itions		
Operating Temperature [°C]	-20 to 40		
Operating Humidity [%]	10 to 80		
Mechanical			
Dimensions (W x H x D) [mm] per module	600 x 337.5 x 29		
Dimensions (W x H x D) [mm]	4,812 x 2,806 x 50		
Weight [kg]	342.8		
Additional Features			
Shipping Content	1x LED Controller; LED Modules (64 Cabinets, 256 Pixel Cards); Overframe Kit (8x8); Pixel Card Removal Tool; Power Bar; Spare Parts Kit; Wall mount (8x8)		
Special Characteristics	Flush Surface SMD Design; Single Data Receiving Cards; Single Power Supplies		
Manufacturer	NEC		
Serviceability	Front Service		
IP Level	IP20		
Certifications	CE; ETL; FCC Class A; RoHS		
Warranty	2 years		

^{* 217} inch

Material

This document is $\ \odot$ 2024 Sharp NEC Display Solutions Europe GmbH.

Aluminum Cabinet

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 17.12.2024